

# AMERICAN COATINGS

## UI 5700 UNICOAT QUICK PATCH

### Product Data Sheet

<b>Type:</b> A two-component, mercaptan cured epoxy.	<b>Volume Solids (Mixed):</b> 100%
<b>Description:</b> Unicoat 5700 is a fast cure epoxy sealing compound.	<b>Weight Solids (Mixed):</b> 100%
<b>Suggested Uses:</b> <ul style="list-style-type: none"><li>• Quick set temporary adhesive where welding is not possible (adheres to metal or concrete).</li><li>• Stop weeps (leaks) in tanks, vessels, sumps, and pits to allow successful application of caulk such as Unicoat 5300, 5800, or 5900 to an uncontaminated surface.</li></ul>	<b>Weight Per Gallon (Mixed):</b> 10.0Lbs.      4.5 Kg.
<b>Not Recommended For:</b> <ul style="list-style-type: none"><li>• Replacement for welding where structural integrity is required.</li><li>• Potable water</li></ul>	<b>Suggested Dry Film Thickness:</b> As required
<b>Resistance Properties For:</b> Fuels – Excellent Sweet & Sour Crude –Excellent Alkalies – Excellent Gases – Excellent Salts – Excellent Ethanol – Excellent Aviation Fuels – Excellent Most Solvents – Excellent	<b>Gloss:</b> Semi-gloss
<b>Compatibility With Other Coatings:</b> Unicoat 5700 is self priming. After curing 4-5 minutes, if no leak is observed, clean area to be caulked and apply specified product.	<b>Colors:</b> Off – white made from: White Base Yellow Activator
<b>Maximum Service Temperature:</b> 300° F (148° C) (dry).	<b>Flash Point:</b> 200° F (93° C)

All technical advice, recommendations and services are rendered by the seller gratis. They are based on technical data which the Seller believes to be reliable, and are intended for use by persons having skill and know-how at their own discretion and risk. Seller assumes no responsibility for results obtained or damages incurred from their use by Buyer in whole or in part. Such recommendations, technical advice or service are not to be taken as a license to operate under or intended to suggest infringement of any existing patent.